

LIPSTICK <STICK> LS-16-2

ELDEW™ PS-203 and PS-306 gives high gloss and strength.

By adding a small amount of **ELDEW™** PS-304, you can reduce stickiness while giving the stick flexibility.

	Trade name	INCI Name	wt %	Function
A	ELDEW™ PS-203	Phytosteryl/Octyldodecyl Lauroyl Glutamate	10.0	Emollient
	ELDEW™ PS-306	Phytosteryl/Behenyl/Octyldodecyl Lauroyl Glutamate	10.0	Emollient
	COSMOL 222 *1	Diisostearyl Malate	13.0	Emollient
	TCG-M *2	Caprylic/capric triglyceride	13.0	Emollient
	PARLEAM 18 *3	Hydrogenated polyisobutene	12.0	Emollient
	LISONOL 20SP *2	Octyldodecanol	7.0	Emollient
	SALACOS 5418V *1	Pentaerythrityl Tetraisostearate	8.0	Emollient
	DOWSIL™ SH 556 Fluid *4	Phenyl trimethicone	5.0	Emollient
	PMWAX 82 *5	Polyethylene	6.0	Binder
	PMWAX 82 *5	Microcrystalline wax	2.0	Binder
	ELDEW™ PS-304	Phytosteryl/Behenyl/Octyldodecyl Lauroyl Glutamate	2.0	Binder
В	DK-PGT Paste R7 *6	Polyglyceryl-2 Triisostearate, Red 7 (CI 15850)	4.0	Coloring
	DK-PGT Paste IOR *6	Polyglyceryl-2 Triisostearate, Iron Oxides (CI 77491)	2.0	Coloring
	DK-PGT Paste Ti *6	Polyglyceryl-2 Triisostearate, Titanium oxide	2.0	Coloring
	Total			

^{*1} Nisshin Oilio *2 Kokyu Alcohol Kogyo *3 NOF *4 Dow chemical *5 Nikko Rika

<PROCEDURE>

- 1. Part B was mixed with roll mill.
- 2. Part A was stirred at 100 °C until uniform.
- 3. After confirming that Part A has become transparent, add Part B and stir at 100 °C for 30 minutes.
- 4. Fill a lipstick container and cool in a refrigerator at 5 °C for about 20 minutes.
- 5. Take out and complete.

<PHYSICAL PROPERTIES and STABILITY>

Appearance: Stick

Recommended container: sleeve type

Maximum load: 140g (FUDOH RHEOMETER: Range 2kg, Adapter T shape, Speed

30cm/min, Distance from base of container 15mm, 25°C)

Stability: -5 °C, 25 °C, 40 °C, Cycle for 1month

Note; The information is provided based upon our technical data and present knowledge. However, we make no warranties, expressed or implied, and assume no liabilities in connection with any use of the information with respect to specific property, safety and suitability for a specific application. It is also not guaranteed that use of the information does not fall within the scope of any intellectual property rights.

^{*6} DAITO KASEI