

MAKE-UP PRIMER <W/O> STPR-K

Make-up primer containing **AMIHOPE™ SB-103** shows an excellent adhesiveness spreadability to the skin and provides a wrinkle-blurring effect.

	Trade Name	INCI Name	wt%	Function
A	MARUKAZOL R *1	Isododecane	9.0	Solvent
	CROPURE JOJOBA *2	Jojoba Oil	3.4	Solvent
	SUGAR SQUALANE *3	Squalane	3.4	Solvent
	ELDEW™ SL-205	Isopropyl Lauroyl Sarcosinate	0.7	Emollient, Sensory improver
	POLYAQUOL OS2 *4	Polyglyceryl-2 Oleate, Polyhydroxystearic Acid, Polyglyceryl-2 Stearate	2.0	Emulsifier
	POLYAQUOL VO4 *4	Polyglyceryl-4 Oleate, Polyglyceryl-6 Oleate, Polyhydroxystearic Acid	1.0	Emulsifier
	NIKKOL HEXAGLYN PR-15 *3	Polyglyceryl-6 Polyricinoleate	1.0	Emulsifier
	BENTON GEL ISD V *5	Isododecane, Disteardimonium Hectorite, Propylene Carbonate	4.0	Gelatinizing agent
	UNIMER U-15 *6	VP/Eicosene Copolymer	1.0	Film-forming agent
UVINUL MC 80 *7	Ethylhexyl Methoxycinnamate	4.0	UV absorber	
B	NAI-TR-10 *8	Titanium Dioxide, Aluminum Hydroxide, Disodium Stearoyl Glutamate	1.0	Pigment
	NAI-RPS-10 *8	Iron Oxides, Disodium Stearoyl Glutamate, Aluminum Hydroxide	0.03	Pigment
	NAI-YP-10 *8	Iron Oxides, Disodium Stearoyl Glutamate, Aluminum Hydroxide	0.15	Pigment
	NAI-BP-10 *8	Iron Oxides, Disodium Stearoyl Glutamate, Aluminum Hydroxide	0.01	Pigment
	POLYAQUOL OS2 *4	Polyglyceryl-2 Oleate, Polyhydroxystearic Acid, Polyglyceryl-2 Stearate	1.0	Dispersing agent
	COSMOL 43V *9	Polyglyceryl-2 Triisostearate	5.0	Dispersing agent
C	AMIHOPE™ SB-103	Tapioca Starch, Lauroyl Lysine	3.0	Sensory Improver
D	PROPANEDIOL *10	Propanediol	9.0	Moisturizer
	MALTITOL	Maltitol	3.0	Moisturizer
	PHENOXYETHANOL	Phenoxyethanol	0.4	Preservative
	WATER	Water	47.9	Solvent
Total			100.0	

*1 MARUZEN SEKIYU, *2 CRODA, *3 NIKKO CHEMICALS, *4 INNOVACOS, *5 ELEMENTIS, *6 GIVAUDAN, *7 BASF, *8 MIYOSHI, *9 NISSIN OILIO, *10 PRIMIENT COVATION LLC

<PROCEDURE>

- Disperse part B with a roller mill 3 times.
- Mix part A uniformly at 75°C.
- Add part C into part A and mix well.
- Add part B into part (A+C) and mix part (A+B+C) with a homogenizing mixer (3,000 rpm, 5 min) at 75°C.
- Mix part D uniformly at 75°C.
- With adding part D into part (A+B+C) gradually, mix them with a homogenizing mixer for 5 min.
- Cool down by stirring with a paddle mixer (150 rom) at room temperature.

<PHYSICAL PROPERTIES and STABILITY>

Appearance: Paste

Viscosity: 2,000 mPa·s (B type rotor No. 3, 12rpm, 30sec, 25°C)

Stability: -5°C, 0°C, 25°C, 40°C, 50°C, Cycle (-5°C⇄40°C), 1 Month



Note; The information is provided based upon our technical data and present knowledge. However, we make no warranties, expressed or implied, and assume no liabilities in connection with any use of the information with respect to specific property, safety and suitability for a specific application. It is also not guaranteed that use of the information does not fall within the scope of any intellectual property rights.